





TECH ACTIV - FLEX S3

Réf. : 70710



Suitable for :	Inside/Outside
Type :	Low shoe
Activity :	Manufacturing and assembly / Environment / Electronic Industry, ESD
Upper :	Water resistant full supple leather and CORDURA® material
Lining :	ARTICO® blue color, up to the toes, slipper feeling
Tongue :	Bellows tongue in ON STEAM® microfiber, lining ARTICO® and padded 10mm thick foam
Ankle protection :	
Fastening :	Flat polyester laces, brown color
Toe cap :	Ultralight and extra wide 200 joules, Composite LIGHT SYSTEM®
Midsole :	Composite FLEX SYSTEM®, anti-magnetic and thermal insulated
Insole :	Thermoformed in active carbon dual density foam, antistatic, ESD and antibacterial FRESH TECH®
Sole :	PU 2D, TECH SOLE® ankle anti-twist system, oil resistant FO, antistatic, HI-CI
Sole pattern :	Multi-purpose cleated indoor/outdoor outsole, well-defined heel, cleated arch, SRC standard
Weight (Kg/pair) :	1.000
Colors :	Brown/blue upper and brown/dar grey outsole
Sizes :	35-48 (2-13)
Standard :	EN ISO 20345:2011 SRC / EN 61340-5-1 / DGUV 112-191
CE certificate of conformity N° :	0075/020/161/08/17/1266 - EXT 11/09/17
Special features :	Lateral reflective piece
Special features 2 :	
Special features 3 :	

SPECIAL FEATURES




-  Integral 100% composite (Air System + Light System + Flex System)
-  Metal free, non magnetic
-  Water absorption and penetration resistance of upper (WRU)
-  Electro Static Discharge Standard EN 61340-5-1

CORDURA



Double II
ARTICO

GENERAL FEATURES

-  Antistatic properties (A)
-  Heel energy absorption (E)
-  Abrasion resistance
-  Crampon sole
-  Heat-insulated sole (HI)
-  Cold-insulated sole (CI)
-  200 joule extra-wide toecap
-  Hyper-ventilated lining
-  Perforation-resistance 1100 N (P)