






TECH CONSTRUCTOR - S3

Réf. : 70114



| | |
|--|---|
| Suitable for : | Outside |
| Type : | Ankle shoe |
| Activity : | Construction / Electronic Industry, ESD |
| Upper : | Water resistant supple nubuck leather and CORDURA® material |
| Lining : | ARTICO® black color, up to the toes, slipper feeling |
| Tongue : | Bellows tongue in ON STEAM® microfiber, lining ARTICO® and padded with 10mm thick foam |
| Ankle protection : | CORDURA® material, ling ARTICO® and padded with 10mm thick foam |
| Fastening : | Metal hooks and round polyester black laces |
| Toe cap : | Ultralight and extra wide 200 joules, Composite LIGHT SYSTEM® |
| Midsole : | Stainless steel |
| Insole : | Thermoformed in active carbon dual density foam, antistatic, ESD and antibacterial FRESH TECH® |
| Sole : | PU 2D, TECH SOLE® ankle anti-twist system, oil resistant FO, antistatic, HI-CI |
| Sole pattern : | Multi-purpose cleated indoor/outdoor outsole, well-defined heel, cleated arch, SRC standard |
| Weight (Kg/pair) : | 1.200 |
| Colors : | Black upper and dark grey/black outsole |
| Sizes : | 35-48 (2-13) |
| Standard : | EN ISO 20345:2011 SRC / EN 61340-5-1 / DGUV 112-191 |
| CE certificate of conformity N° : | 0075/020/161/08/17/1266 - EXT 14/09/17 |
| Special features : | Reinforced at the front with PU coated microfiber, abrasion resistant material (waterproof stitching) |
| Special features 2 : | Especially studied for Construction & Publics works |
| Special features 3 : | |

SPECIAL FEATURES










-  200 joules light composite toecap
-  Water absorption and penetration resistance of upper (WRU)
-  Electro Static Discharge Standard EN 61340-5-1

CORDURA

on steam

Double III ARTICO

G GENERAL FEATURES

-  Antistatic properties (A)
-  Heel energy absorption (E)
-  Abrasion resistance
-  Crampon sole
-  Heat-insulated sole (HI)
-  Cold-insulated sole (CI)
-  200 joule extra-wide toecap
-  Hyper-ventilated lining
-  Perforation-resistance 1100 N (P)